ARMOVEX DURAVEX™ 9500

Advanced Concrete Protection Sealer

PRODUCT DESCRIPTION

ARMOVEX DURAVEX™ 9500 is a water-based Polyacrythane™ protective treatment designed to enhance the durability, stain resistance, and weatherability of concrete, masonry, pavers, and other cementitious substrates.

Unlike conventional sealers that rely solely on surface film formation or penetrating chemistry, DURAVEX 9500 creates a durable protective barrier that resists water intrusion, chemical attack, UV degradation, freeze-thaw damage, and surface wear while maintaining the natural appearance of the substrate.

RECOMMENDED USES

Concrete driveways, sidewalks, decorative concrete, stamped concrete, exposed aggregate, pavers, patios, pool decks, parking structures, CMU block, masonry surfaces, and industrial concrete floors.

KEY BENEFITS

- Advanced Polyacrythane™ technology
- Excellent water repellency
- Stain resistance
- UV stable and non-yellowing
- Helps reduce freeze-thaw deterioration
- Improves surface durability
- Breathable formulation
- Low odor
- Environmentally friendly
- Suitable for interior and exterior applications

SURFACE PREPARATION

Surface must be structurally sound, clean, and free of dust, dirt, oils, curing compounds, sealers, coatings, efflorescence, and other contaminants that may interfere with performance.

DURAVEX™ 9500 may be applied to new or existing concrete provided the substrate has developed sufficient strength and is free of excess moisture. Always perform a test area to verify desired results and compatibility.

Remove loose or deteriorated material prior to application. Mechanically clean or pressure wash surfaces as necessary. Allow surfaces to dry before application. Repair significant cracks, spalls, or structural defects prior to treatment.

APPLICATION

Apply using a low-pressure sprayer, microfiber applicator, roller, or brush. Apply evenly and avoid puddling. Multiple light applications are preferred over heavy applications.

COVERAGE RATE

Coverage varies depending on surface porosity and texture.

Typical Coverage: 300 – 500 sq ft per gallon per coat.

LIMITATIONS

- Do not apply to standing water.
- Do not apply if rain is expected within 24 hours.
- Do not apply below 40°F (4°C). Protect from freezing.
- Test on a small area prior to full application.

WARRANTY

ARMOVEX warrants this product to be free from manufacturing defects. Liability is limited to replacement of defective material.